

SPECIFICATIONS

Current Rating: 1 Amp
 Insulator resistance: 5000 Megohms min.
 Dielectric withstanding: AC 500 V
 Operating Temperature: -40°~+105°C
 Max Processing Temp: 230° for 30 seconds
 Contact Material: Copper alloy
 Insulator Material: Polyester, UL 94V-0
 ◎Standard: Nylon-6T
 Finish: Gold plated
 ◎Standard Gold flash all over

*Product specifications are subject to change without notice. Please contact sales office for further confirmation.

PDOS-50-X-146


Pin type: Brass, Bronze, Phosphor Bronze, ◎Standard: L

Pin Length mm: L, B, P

Contact Plating: Definition, Code

Number of Contacts: ◎ Gold plated, flash B, ◎Standard: B

▲ 1.00	VERSION	1.00±0.20	12-28-98*
▲ 1.00	VERSION	1.00±0.20	12-28-98*
▲ 3.15	VERSION	3.35±0.10	12-28-98*
▲ 1.80	VERSION	1.85	12-28-98*
▲ 3.80	VERSION	3.85	12-28-98*
▲ XDPOS2-50-XXX-14.6	VERSION	NPDOS-50-X-146	26-06-01*



GENERAL TOLERANCE	
XX. ±	XXX. ±
X. ±	.XXX ±
.X ±	.X* ±
.XX ±	.X* ±

SCALE	3=1
UNIT	MM
SIZE	A4

DRAWN	CHECK	APPROVE
-------	-------	---------

DATE	-06-01'
DATE	-06-01'
DATE	-06-01'

DWG. NO.	F:\DWG\CDWG\PDOS\PDOS0B.DWG
PARTS NO.	PDOS-50-X-146

TITLE	PDOS Series
-------	-------------

REV.	1.2
SHEET	1/2